NEW

Helps Extend the Life of Hydraulic Tools!



The ESCO Air Reducer, for Air/Hydraulic Pumps, is designed to regulate the air pressure that is received by the hydraulic pump, that is then used to power all **ESCO Hydraulic Tools.**

Maintaining air pressure when using Hydraulic Equipment will increase the Proper Functioning of Hydraulic Equipment, Protect Air/Hydraulic Pumps from Over-Flow of Air, & Keep ESCO Hydraulic Products in their PRIME.

- Maintain Reccommended working Air Pressure.
- Easy Installation & Usage
- 10601K Comes with Air Reducer & Whip-Hose (ESCO Model #10601H)
- Can be used in conjunction with multiple ESCO Products.
- Diameter: 15/16" 24
- **Working Air Pressure: 110 PSI**
- Air Inlet Size: 1/4" NPT
- Shipping Weight: 1 lb. 0.5 kg

OFFERING

10601K Air Reducer will be included with ALL **Hydraulic Pump & Bead Breaker Kits!**





MODEL 10601K being used on ESCO 10500 Hydraulic Pump to regulate air pressure down to the manufacturer suggested 110 psi.

ESCO 3.5 Quart Turbo II Air Hydraulic Pump

Model #10500



- 3.5 quart oil capacity.
- Rugged, Lightweight Plastic Reservoir with polyglass sight gauge.
- 10,000 psi hydraulic pressure.
- Easily works on rams and bead breakers with oil to
- Compact design easily fits storage bins.
- FASTEST PUMP AVAILABLE.
 - Shipped with premium hydraulic oil.
- Weight: 18 lbs. 8 kg

MODEL 10501

S

10500 - Turbo II Air Hydraulic Pump 3 1/2 Quart 10610 - Hose Assembly, 8'

10601K - Air Reducer, 6" Whip-Hose

MODEL 10501C

10500 - Turbo II Air Hydraulic Pump 3 1/2 Quart 10604 - Hose Assembly with Hose Coupler, 8' 10601K - Air Reducer, 6" Whip-Hose







