

ESCO Steel Cribbing Stands - 3", 6", & 9" Stackers

OSHA



All pieces interlock and can be used individually or stacked together for various lift heights. They will not slide or shift during lifting.

MAXIMUM CAPACITY 55 TONS

Model #	Tonnage	Size	Wgt.
12500	55 50 Tonne	3"6"/9" 76mm/152mm/229mm	141 lbs. 64 kg
12501	55 50 Tonne	3" 76mm	38 lbs 17 kg
12502	55 50 Tonne	6" 152mm	47 lbs 21 kg
12503	55 50 Tonne	9" 229mm	56 lbs 25 kg



ESCO Support Plates- For Use with Jacks to Create Stability

OSHA



MODEL 10751



MODEL 10753



MODEL 10754



MODEL 10752

- CORROSION PROOF
- LIGHTWEIGHT
- LIFETIME WARRANTY

- ▶ No more cracked, warped, bulky wooden blocks.
- ▶ Lightweight, Corrosion & Rot-Proof
- ▶ Will Not Absorb Moisture.
- ▶ Up to 100 Ton weight capacity.
- ▶ Will not break under load, mushroom, or warp.
- ▶ Works with all types of jacks and doubles the surface area for the jack to sit on.
- ▶ Great in soft earth or uneven ground.
- ▶ Lifetime guarantee against breakage.
- ▶ Allows Employer to comply with OSHA Regulation 29 CFR 1926.305 "Blocking for a Firm Foundation"



Jack Not Included

Model #	Tonnage	Size	Wgt.
10751	55 50 Tonne	12"x12"x1" 305x305x25mm	5 lbs. 2 kg
10752	25 22 Tonne	18"x18"x1" 457x457x25mm	11 lbs. 5 kg
10753	20 18 Tonne	12"x12"x1" 305x305x25mm	5 lbs. 2 kg
10754	100 90 Tonne	12"x12"x1" 305x305x25mm	6 lbs. 2 kg
10755	20/55/100 18/50/90 Tonne	12"x12"x1" 305x305x25mm	16 lbs. 7 kg