

**COMPAC 2 Ton Jack - Low Height Floor Jack w/ Foot Pedal**


Model #90530



MODEL 90530

- ▶ Ergonomically designed handle for operator comfort. Rubber Coated.
- ▶ Easy "Lift-and-Turn" lowering system prevents unintentional lowering.
- ▶ Additional foot pedal pumping feature provides fast saddle raising to the load.
- ▶ Safety lowering control valve for safe lowering even under maximum load.
- ▶ Accessories available for this an other Compac Units. See *Accessories section for more details.*

<b>Max (Ton)</b>	2 TON	<b>C</b>	28.74" 730 mm
<b>Weight</b>	82 lbs. 37 kg.	<b>D</b>	6.3" 160 mm
<b>A</b>	3.15" 80 mm	<b>E</b>	14.96" 380 mm
<b>B</b>	19.69" 500 mm	<b>F</b>	36.42" 925 mm



**COMPAC 3 Ton Jack - Low Height Jack for Vans, 4WD, & Minibuses**


Model #90531



MODEL 90531

- ▶ Ergonomically designed handle for operator comfort. Rubber Coated.
- ▶ Easy "Lift-and-Turn" lowering system prevents unintentional lowering.
- ▶ Additional foot pedal pumping feature provides fast saddle raising to the load.
- ▶ Safety lowering control valve for safe lowering even under maximum load.
- ▶ Accessories available for this an other Compac Units. See *Accessories section for more details.*

<b>Max (Ton)</b>	3 TON	<b>C</b>	39.96" 1015 mm
<b>Weight</b>	93 lbs. 42 kg.	<b>D</b>	6.69" 170 mm
<b>A</b>	4.53" 115 mm	<b>E</b>	14.96" 380 mm
<b>B</b>	19.69" 500 mm	<b>F</b>	36.42" 925 mm



**COMPAC 1.5 Ton Jack - High Lift Jack w/ Bogie Wheels & Ft. Pedal**

Model #90532



MODEL 90532

- ▶ Ergonomically designed handle for operator comfort. Rubber Coated.
- ▶ Easy "Lift-and-Turn" lowering system prevents unintentional lowering.
- ▶ Additional foot pedal pumping feature provides fast saddle raising to the load.
- ▶ Long reach chassis improves access to lifting points deep under vehicle.
- ▶ Bogie system is ideal for workshops with uneven floors and outdoors - where small obstacles and gratings are easily crossed.

<b>Max (Ton)</b>	1.5 TON	<b>C</b>	43.9" 1115 mm
<b>Weight</b>	126 lbs. 57 kg.	<b>D</b>	6.3" 160 mm
<b>A</b>	4.33" 110 mm	<b>E</b>	14.96" 380 mm
<b>B</b>	31.5" 800 mm	<b>F</b>	36.42" 925 mm

