

Digital Wall Mounted Tire Inflator - Wall Mountable Inflation System

Model #10964



- O **Wall Mountable Auto Air Inflation System**
- 2 **Heavy Duty Metal Housing**
- 3 Large Backlit LCD Display with Audible Warning
- 32 ft. Single Straight (Clip On) Air Hose Included)
- Programable Pre-Set Functions (P1 & P2) for quick use with common inflation values.
- Comprehensive Diagnostics & Error Reports
- Inflates accurately with hose length up to 165 ft | 50 m
- Operation: Inflate, Deflate, & Measure Air Pressure
- Advised Application: Indoor Industrial, Workshops
- Supply Voltage: 110V
- Wattage: 12 W Max.

| Max. Inflation | 174 psi <i>12 bar</i> |
|---------------------|----------------------------------|
| Scale | 174 psi/ 12 bar/ 1200 Kpa/ 12kgF |
| Inlet Size | 1/4" NPT |
| Hose Length | 32 ft. 10 m |
| Weight | 4.6 lbs. 2.3 kg |
| Accuracy | +/- 0.3 psi @ 25-75psi |
| Supply Pressure Max | 182 nsi l 12 55 har |

Digital Wall Mounted Tire Inflator - Wall Mountable Inflation System

Model #10965



Wall Mounted Tire Inflation System w/ 4-Hose Manifold*



*For Manifold Only w/ (4) 25' Hoses- Model 10967

Standard inflate/deflate (auto) - Over pressure for Tire shops; where new tires are fitted and you need to ensure that the tire inflates to a pressure where the tire seats properly on the rim then deflates automatically to the required preset pressure.

Flat Tire: where there is no residual tire pressure in the tire the inflator does not automatically start so a manual override is required to fill flat tires.

Built tough to last this unit is IP56 rated so it can withstand the elements inside and out, it has mechanical anti-vandal buttons and a loud audible warning that can be heard in the noisiest areas when the correct Tire pressure has been reached.

- Aluminum Die-Cast Housing
- Mechanical Anti-Vandal Buttons
- IP56 Rated for Indoor and Outdoor Use
- OPS System Audible Warning
- Comprehensive Diagnostics and Error Reporting
- Will Inflate Accurately with Hose Lengths up to 164 ft.

| Chuck type | Clip on |
|----------------------|-----------------------------------|
| Chuck style | Single straight |
| Scale | 0-145 psi, 0.5-10 bar, 0-1000 kPa |
| Inlet size | 1/4" NPT female |
| Hose length | 25 ft. 7.5 m |
| Weight | 12 lbs. 5.5kg |
| Accuracy* | +/- 0.3 psi @ 25-75 psi |
| Operation | Auto Inflate, Deflate |
| Supply pressure max. | 182 psi |
| Advised application | Industrial, workshops, outdoor |
| Supply voltage | 110V |
| Wattage | 12 W Max. |
| Humidity range | Up to 95% RH non condensing |
| Inflation speed | 106 cfm 3000 L/ min @ 182 psi |