

AUTOMATIC HD Tire Inflation Cage - 78" OD Safety Inflation Cage

Model #90423



MODEL 90423

- ▶ The heavy duty tire inflation cage is used to inflate tires for trucks, military vehicles, tractors and aircrafts.
- ▶ Specially equipped with an automatic tire Inflator to make the cage even safer. You can inflate up to 195 PSI 13.5 bar.
- ▶ Equipped, on both of its doors, of a safety system that activates or deactivates the inflation of the tire. If one of the doors is open, the automatic tire Inflator will not be activated. You must close the 2 doors properly in order to inflate.
- ▶ HD inflation cage is equipped with an air hose and power cable (110 Volt).

Dimensions (L x W x H)	Max. Tire Size	Weight
91" x 51" x 78" 2083mm x 1016mm x 1982mm	78" OD x 35" W 1980mm OD x 889mm W	1150 lbs. 523 kg.

AUTOMATIC HD Tire Inflation Cage - 82" OD Safety Inflation Cage

Model #90424



MODEL 90424

- ▶ The heavy duty tire inflation cage is used to inflate tires for trucks, military vehicles, tractors and aircrafts.
- ▶ Specially equipped with an automatic tire Inflator to make the cage even safer. You can inflate up to 195 PSI 13.5 bar.
- ▶ Equipped, on both of its doors, of a safety system that activates or deactivates the inflation of the tire. If one of the doors is open, the automatic tire Inflator will not be activated. You must close the 2 doors properly in order to inflate.
- ▶ HD inflation cage is equipped with an air hose and a power cable (110 Volt).

Dimensions (L x W x H)	Max. Tire Size	Weight
84" x 56" x 82" 2134mm x 1423mm x 2083mm	82" OD x 50" W 2083mm OD x 1282mm W	1324 lbs. 602kg.

AUTOMATIC OTR & Mining Tire Inflation Cage

Model #90425



MODEL 90425

- ▶ The largest inflation safety cage ever built in the world.
- ▶ Handles tires with diameter up to 115" | 2921mm. Mining & OTR tires ranging from 24.00R49 to 45/65R/45 and even 30.00R51.
- ▶ The Cage itself weighs more than 6,500 lbs. | 2949 kg
- ▶ Hot Dipped Galvanized, this cage is manufactured to withstand temperatures ranging from - 22° F | -30° C to 122° F | 50° C.
- ▶ Equipped, on both of its doors, of a safety system that activates or deactivates the inflation of the tire. If one of the doors is open, the automatic tire Inflator will not be activated. You must close the 2 doors properly in order to inflate.
- ▶ HD inflation cage is equipped with an air hose and a power cable (110 Volt).

Dimensions (L x W x H)	Max. Tire Size	Weight
136" x 72" x 130" 3454mm x 1829mm x 3302mm	115" OD x 48" W 3000mm OD x 1219mm W	8998 lbs. 4090 kg.