Giant Tire/Earthmover Bead Breaker

Model #10100

OSHA



Alignment Screw

Jaw/Hook

Clevis Support

13.8 Tons of Bead Breaking Force, 4" Stroke. | 102mm

Use on 5-piece rims 25" to 51" with pry bar/bead loosing pockets. Ram will break the toughest of beads. Use with 10,000 PSI Hydraulic Pump. Weight 31 lbs. | 14 kg

MODEL 10209

10100 - Giant Tire Bead Breaker Tool 10592 - Pump, Air Hydraulic, 5 quart

10604 - Hose Assembly with Hose Coupler, 8' 10601K - Air Reducer, 6" Whip-Hose

MODEL 10207


10100 - Giant Tire Bead Breaker Tool

10500 - Turbo II pump, Air Hydraulic, 3 1/2 Quart

10604 - Hose Assembly with Hose Coupler, 8'

10601K - Air Reducer, 6" Whip-Hose





 Allows bead breaker to be tightened against a flat surface

 Fits all style earth mover bead breakers, except:

#10104 (Goodyear TO-100) #10103 (Goodyear TO-2000)



MODEL 10607

MODEL 10209



MODEL 10207








Model #10896





- 4.25" Stroke | 108mm
- 13.8 Ton Ram will break the toughest beads
- Used with 10,000 psi air hydraulic pumps
- Weight: 29 lbs. | 13 kg



Point.Scan.Explore.

MODEL 10822

10896 - Giant Tire Bead Breaker Tool 10875 - Pump, Air Hydraulic, 5 Quart

10604 - Hose Assembly with Hose Coupler, 8'

10601K - Air Reducer, 6" Whip-Hose

MODEL 10823

10896 - Giant Tire Bead Breaker Tool

10877 - Metal Pump, Air Hydraulic, 5 Quart

10604 - Hose Assembly with Hose Coupler, 8'

10601K - Air Reducer, 6" Whip-Hose



MODEL 10822



MODEL 10823