

The **MAMMUT RANGE OF JACKS** offers service professionals a solution that is safe and easy to use, for all those operations to lift earthmoving, construction, quarry, and mining machinery, where maintenance requires professional skills and expertise. All models are air/hydraulic operated and equipped with a dual descent valve for greater control when bearing weight and automatic piston return; they can also be fitted with a manual emergency pump (on request).

Specifications





A	69.2 in 1757 mm
В	27.8 in 708 mm
С	49.3 in 1253 mm
D	39.3 in 1000 mm
E	25.5 in 650 mm

Accessories



Model	Description	Specs
91035	Extension Holder R	NA
91034	Extension Holder L	NA
91049	Tilting Plate	A: 3 in B: 2.125 in A: 77mm B: 55mm
91029	Extension	A: 7.875 in B: 2.125 in C: 2.125 in A: 200mm B: 55mm C: 55mm
91030	Extension	A: 9.875 in B: 2.125 in C: 2.125 in A: 250mm B: 55mm C: 55mm
91031	Extension	A: 11.875 in B: 2.125 in C: 2.125 in A: 300mm B: 55mm C: 55mm
91009	Safety Lock Holder	Safety Lock Holder (4) Safety Block (H) 4 - (W) 9.875 in Safety Block (H) 2 - (W) 9.875 in

NOTE: ESCO reserves the right to change, alter, or modify product(s) without notice. This includes but is not limited to product: color, design, parts, accessories, etc.

sales@esco.net WWW.ESCO.NET 1.800.352.9852











