

The **MAMMUT RANGE OF JACKS** offers service professionals a solution that is safe and easy to use, for all those operations to lift earthmoving, construction, quarry, and mining machinery, where maintenance requires professional skills and expertise. All models are air/hydraulic operated and equipped with a dual descent valve for greater control when bearing weight and automatic piston return; they can also be fitted with a manual emergency pump (on request).

Specifications

MAMMUT





Α	68.9 in 1751 mm	
В	25.3 in 644 mm	
С	48.1 in 1222 mm	
D	57.7 in 1466 mm	
E	35.4 in 900 mm	

Accessories



Model	Description	Specs
91035	Extension Holder R	NA
91034	Extension Holder L	NA
91049	Tilting Plate	A: 3 in B: 2.125 in A: 77mm B: 55mm
91029	Extension	A: 7.875 in B: 2.125 in C: 2.125 in A: 200mm B: 55mm C: 55mm
91030	Extension	A: 9.875 in B: 2.125 in C: 2.125 in A: 250mm B: 55mm C: 55mm
91031	Extension	A: 11.875 in B: 2.125 in C: 2.125 in A: 300mm B: 55mm C: 55mm
91047	Safety Lock Holder	Safety Lock Holder (4) Safety Block - (H) 4 in - (W) 6 in Safety Block - (H) 2 in - (W) 6 in

NOTE: ESCO reserves the right to change, alter, or modify product(s) without notice. This includes but is not limited to product: color, design, parts, accessories, etc.

sales@esco.net WWW.ESCO.NET 1.800.352.9852





91047







