HD COMMERCIAL TRUCK Stud/Hub Cleaner MODEL 50172





WHY USE THE ESCO HD STUD/HUB CLEANING TOOL?

Contaminates (Rust, Corrosion, Debris, etc.) can cause the wheel to not be properly torqued onto the wheel face, which can cause the wheel to be out of balance, uneven tire wear, damaging of wheel and or wheel face, or worse, potential wheel off situations.







designed for used on medium trucks with stud sizes of 3/4 in & 22mm

EASILY REPLACE HUB/STUD PAD

PUSH TAB DESIGN FOR FAST AND EASY PAD REPLACEMENT

	Model # Description	50172 HD STUD KLEEN
A	Pad Diameter	2 7/16 in. 62mm
В	Pad Height	3/16 in. 4.8mm
С	Total Tool Length (w/out pad)	5 1/8 in. 130mm
	Maximum Stud Length	5 3/4 in. 146mm
	Rotations Per Min. Max.	12,000 RPM
	Drive Size	1/2 inch Drive



BENEFITS & FEATURES:

- ▶ **NEW:** Easy to replace stud/hub cleaning pad design.
- ▶ Removes Rust, Corrosion and other Debris that builds up on the tire rim, wheel stud, hub, rotors, and brake drum with ease.
- Fast and Easy to Use Lightweight cleaning pads are exceptionally tough and will remove rust and other corrosion with ease Will Not damage studs or other steel components.
- ▶ **Long Lasting** Can be used on up to 150 hub/stud combinations.
- Hundreds of Internal Stainless Steel Tines Clean off debris that has built up on studs, removing rust and increasing accuracy of torquing when putting wheel(s) back onto vehicle.
- Abrasive Synthetic Cleaning Pads Rugged and Heavy Duty construction longer lasting than other competitive brands.
- ▶ **Application** Designed for used on medium trucks with stud sizes of 3/4 in & 22mm.

REPLACEMENT PADS AVAILABLE:





1-PIECE MODEL 50175

4-PACKMODEL 50176



USE WITH IMPACT WRENCH

Compatible with air or electric $\frac{1}{2}$ " impact, the HD Stud Kleen's solid structure allows for quick and easy use and storage in shops, garages, or fleet service trucks.



SAVE TIME

Uniquely designed to clean both the wheel surface and studs, preventing the use of multiple tools. HD Stud Kleen maximizes efficiency by securely affixing to impact guns to blast away rust and debris with one heavy-duty tool.



KEEP TIRE/WHEEL RUNNING TRUE

Accurate tire mating requires the wheel and studs to be clean and free from particulates to obtain proper torque. Accurate torque often prevents potential vibrations and seized rims.



CLEANS HUB & STUDS

Replace the traditional use of wire brushes and grinders while thoroughly cleaning the wheel surface and studs. Maintaining clean, rust-free hubs, studs and wheel surfaces allows for accurate mating of the wheel and hubs, required for effective toraue.

NOTE: ESCO reserves the right to change, alter, or modify product(s) without notice. This includes but is not limited to product: color, design, parts, accessories, etc.

sales@esco.net WWW.ESCO.NET 1.800.352.9852











