

AIR/MANUAL HYDRAULIC BOTTLE JACK - commercial-grade construction

model 10380 | 10381 | 10382 | 10383



MANUAL LIFTING FUNCTION

Designed to be operated using air or manually with included two-piece lifting/lowering handle.

ADJUSTABLE EXTENSION SADDLE


Heat Treated Adjustable Extension Screw provides additional and precise height adjustments. Assists in not over extending cylinder to reach designated heights.



WELDED BASE

HD WELDED CYLINDER BASE

Fully welded cylinder & frame provide superior strength and extended service life. (Easy & controlled lowering with included handle)



SPECIFICATIONS:	10380	10381	10382	10383
Capacity	12 Ton (24,000 lbs.)	20 Ton (40,000 lbs.)	20 Ton (40,000 lbs.)	30 Ton (60,000 lbs.)
Minimum Height	9.75 in. 247.7 mm	10 in. 354 mm	7.125 in. 181 mm	10.875 in. 276.2 mm
Maximum Height	18.5 in. 457.2 mm	20 in. 508 mm	12.625 in. 320.7 mm	20 in. 508 mm
Ram Travel	5.75 in. 317.5 mm	6 in. 152.4 mm	3.25 in. 82.6 mm	6 in. 152.4 mm
Screw Adj	3.25 in. 82.6 mm	4 in. 101.6 mm	2.5 in. 63.5 mm	3.75 in. 93.3 mm
Saddle Width	1.75 in. 44.5 mm	1.75 in. 44.5 mm	1.75 in. 44.5 mm	1.75 in. 44.5 mm
Base Thickness	1.25 in. 31.8 mm	1.25 in. 31.8 mm	1.25 in. 31.8 mm	1.75 in. 44.5 mm
Base Size L x W	8.25 x 5.375 in. 204.5 x 136.5 mm	8.875 x 5.75 in. 225.4 x 146 mm	8.25 x 5.75 in. 204.5 x 146 mm	9.625 x 7.125 in. 244.5 x 181 mm
Outer Package Dimensions	10 x 7 x 11 in. 254 x 178 x 279 mm	10 x 8 x 11 in. 254 x 203 x 279 mm	15 x 8 x 8 in. 381 x 203 x 203 mm	11 x 10 x 12 in. 279.4 x 254 x 305 mm
Net Weight	33 lbs. 15 kg	41 lbs. 18.5 kg	34 lbs. 15.5 kg	63 lbs. 29 kg
Gross Weight	34 lbs. 16 kg	42 lbs. 19 kg	35 lbs. 15.9 kg	64 lbs. 30 kg
Air Inlet Fitting	1/4 in. NPT	1/4 in. NPT	1/4 in. NPT	1/4 in. NPT
Air Pressure	110-125 psi 7.5-8.5 bar	110-125 psi 7.5-8.5 bar	110-125 psi 7.5-8.5 bar	110-125 psi 7.5-8.5 bar
Warranty	1-Year Warranty	1-Year Warranty	1-Year Warranty	1-Year Warranty
UPC	816904024857	816904024871	816904024864	816904024888