


## 3-STAGE AIR HYDRAULIC JACK - 50 | 30 | 15 ton capacities

model 10771



**INCLUDES  
STACK-ABLE  
EXTENSIONS**  
for additional height  
& precision lifting.



The **ESCO 3 STAGE AIR/HYDRAULIC SERVICE JACK (MODEL 10771)** is designed for lifting buses, commercial trucks, tractors and farm equipment, and many other low clearance heavy-duty vehicles. This professional grade jack will lift up to 50 tons and has a minimum height of 5.5 in. Unit comes with 3 stackable extensions and extension holders for convenient usage and storage.

- 3 Stages 50T/30T/15T.
- Lifting capacity 50 tons (1st stage), 30 tons (2nd stage), 15 ton (3rd stage).
- Handle length 57.5 in.
- Designed for lifting low buses and other low clearance vehicles.
- Maximum stability and convenient usage.

| SPECIFICATIONS:  | 10771             |
|------------------|-------------------|
| CAPACITY         | 50   30   15 Tons |
| MIN. HEIGHT (A)  | 5.5 in.   140 mm  |
| MAX. HEIGHT (E)* | 35 in.   889 mm   |
| A                | 5.5 in.   140 mm  |
| B (50 T)         | 2.2 in.   56 mm   |
| C (30 T)         | 2 in.   51 mm     |
| D (15 T)         | 2.2 in.   56 mm   |
| E                | 11.9 in. 302 mm   |
| WEIGHT           | 143 lbs.   65 kg  |
| UPC              | 816904022112      |

\*Maximum height without extensions.

## HD TRANSMISSION JACK - 2.2 ton capacity

model 10812



The **ESCO 2.2 TON HEAVY-DUTY TRANSMISSION JACK (MODEL 10812)** is a premium transmission jack designed to handle most any heavy duty transmission. This jack is designed for installing and servicing transmissions up to 2.2 tons or 4,400 lbs. This jack is equipped with 4 swivelling caster wheels to make it easier to roll across concrete garage floors when removing or installing the transmission.

- Wide chassis design provides maximum stability.
- Fully adjustable universal saddle, brackets, and chain sling with left/right tilt (12°) and forward/rear tilt (15°/30°).
- 360° rotatable pump handle for operation in any position with easy access to release valve.
- Sealed hydraulic unit prevents contamination and includes a safety overload system. Conforms to ANSI Standards.

| SPECIFICATIONS: | 10812                    |
|-----------------|--------------------------|
| Capacity        | 2.2 Ton                  |
| Min. Height     | 10 in.   254 mm          |
| Max. Height     | 35 in.   889 mm          |
| Weight          | 35 in.   889 mm          |
| Head Width      | 12-18 in.   305 - 457 mm |
| Head Length     | 16-20 in.   406 - 508 mm |
| UPC             | 816904020156             |