

COMBI STYLE BEAD BREAKER - lightweight aluminum style

model 40801



ALUMINUM
bead breakers



NOTE: The Aluminum Bead Breaker Series from ESCO are designed using aluminum (and steel) components to **reduce the average weight of the unit by 40% compared to an all steel design.**

- Lightweight aluminum construction.
- 10 Tons of bead breaking force.
- Comparable to the steel combi bead breakers.
- To be used on single, and 3-piece wheel assemblies.
- Extended jaw for deep dish style wheels (extended flange).

POPULAR KIT:

MODEL 10245

- 40801** Combi Bead Breaker Tool (Aluminum)
- 10518** Air Hydraulic Pump, 1/2 Gallon
- 10604** Hose Assembly with Hose Coupler, 8 ft.
- 10601-K** Air Reducer, 6 in. Whip-Hose



POPULAR KIT:

MODEL 10246

- 40801** Combi Bead Breaker Tool (Aluminum)
- 10590** Air Hydraulic Pump, 2 1/2 Quart
- 10604** Hose Assembly with Hose Coupler, 8 ft.
- 10601-K** Air Reducer, 6 in. Whip-Hose



MINI BREAKER - small form factor with tons of power

model 40800



ALUMINUM
bead breakers

ALUMINUM
bead breakers

INCLUDED MAGNETIC EXTENSION

Designed to give additional length in difficult situations where additional stroke is needed.

0.80 in. | 20 mm



- Small compact design makes it easy to reach backside of earthmover tires.
- Great for getting between hard to reach dual agricultural tires.
- Detaches inside and outside truck/tractor tire beads from rims.

POPULAR KIT:

MODEL 10247

- 40801** Combi Bead Breaker Tool (Aluminum)
- 10592** Air Hydraulic Pump, 5 Quart
- 10604** Hose Assembly with Hose Coupler, 8 ft.
- 10601-K** Air Reducer, 6 in. Whip-Hose



SPECIFICATIONS:	40800	40801
Ram Tonnage	10 Tons	10 Tons
Material	Aluminum	Aluminum
Rim Sizes	NA	25-57 in. 636-1448 mm
Stroke	1.5 in. 40 mm	2.75 in. 70 mm
Max Pressure	10,000 PSI	10,000 PSI
Length	9.5 in. 241 mm	17 in. 432 mm
Height	7.5 in. 190 mm	13 in. 330 mm
Width	6.3 in. 160 mm	3.5 in. 89 mm
Weight	10.5 lbs. 4.8 kg	19 lbs. 8.5 kg
Warranty	3-Year Warranty	3-Year Warranty
UPC	816904026004	816904022945