

SUPERSEATER BEAD SEATING VALVE(S) - hi-flow male coupler(s)

MODEL 10976 | 10978 | 10988 | 10993



SOLD IN PACKS ONLY



6 PC

STANDARD BORE

model 10976



4 PC

LARGE BORE

model 10978



4 PC

LARGE BORE

model 10988



6 PC

STANDARD BORE

model 10993

SEAT & AIR ANY TIRE FAST & EASY!

- **FASTER, SIMPLE WAY TO SEAT DIFFICULT TIRES:**
Achieve efficient tire seating with ease.
- **50% FASTER THAN TRADITIONAL AIR CHUCKS:**
Reduces time and effort in tire seating.
- Doubles your air volume (CFM) with larger unrestricted passages for optimal performance.
- Best used with certified bead seater tanks like Cyclone or Hurricane for enhanced results.
- Suitable for all demountable tubeless pneumatic wheel assemblies.



**INCREASED
AIR FLOW**



SPECIFICATIONS:	10976	10978	10988	10993
Style	Industrial Type H	Industrial Type G	Industrial Type M	Industrial Type M
Bore Size	Standard Bore	Large Bore	Large Bore	Standard Bore
Coupler Size	3/8 in.	1/2 in.	1/4 in.	1/4 in.
Coupler Style	Male	Male	Male	Male
SCFM	90 psi 6.032 m3/min	90 psi 6.032 m3/min	90 psi 6.032 m3/min	90 psi 6.032 m3/min
Maximum Temperature	From - 4 to 122 F - 20 to 50 C	From - 4 to 122 F - 20 to 50 C	From - 4 to 122 F - 20 to 50 C	From - 4 to 122 F - 20 to 50 C
Maximum Air Inlet	120 psi 8.3 BAR	120 psi 8.3 BAR	120 psi 8.3 BAR	120 psi 8.3 BAR
# of Units	6	4	4	4
Warranty	1-Year Warranty	1-Year Warranty	1-Year Warranty	1-Year Warranty
Net Weight	0.4 lbs. 0.2 kg	0.80 lbs. 0.36 kg	0.19 lbs. 0.8 kg	0.23 lbs 0.10 kg
UPC (Universal Product Code)	816904025786	816904025809	816904025830	816904025847