

COMPACT HD DIGITAL TIRE INFLATOR - with dual end air chuck

MODEL 10962 | 10962-L




**PSI
BAR
KPA**

The **HD COMPACT DIGITAL TIRE INFLATOR** (MODEL 10962) is a single-trigger handheld unit designed for daily use in workshops or on service vehicles. Its easy-to-read digital backlit screen and single-button design make it user-friendly. With an accuracy of +/- 2 psi and a 1-year warranty, this professional inflator is ideal for any inflation task.

- Large digital LCD screen – easy to Read display.
- Compact design – smaller footprint in toolbox, on tool cart, or in service truck.
- MODEL 10962 Comes with dual angle hold-on style chuck with rubber comfort grip for ease of use.
- Features a **holding ring** for both hanging unit in shop and/or service truck.



A



B

AUTO
on/off

AAA
2X

LCD
super clear

**VARIABLE
TEMPERATURE
RESISTANT**

(A) Bright easy to read screen with multi-scale reading capability powered by (2) AAA batteries with easy replacement.

(B) Model 10962-L comes equipped with a **HD+ SEALING AIR CHUCK** which uses a check valve to close the air passage when not in use and opens it for tire inflation, making them essential for inflating tires with a 'live' non-gauged airline.



SPECIFICATIONS: 10962

Reader Unit	1 in. x 1 1/8 in. 25 mm x 28.58 mm
Chuck Type	Hold-On
Chuck Style	Dual Angle
Scale	psi / kPa / bar
Inlet Size	1/4 in. NPT
Hose Length	20 in. 500 mm
Dimensions (L x W x H)	14 (L) x 7 (W) x 3 (H) in. 356 x 177 x 76 mm
Weight	2 lbs. 0.8 kg
Accuracy	+/- 2 psi @ 25-75 psi
Operation	Inflate, Deflate, Measure
Supply Pressure Max.	200 psi 13.79 bar
Advised Application	Industrial, Workshops
Inflation Flow	18 cfm (500 L/min) @ 188 psi
Battery	(2) AAA Included (up to 80 hr battery life)
Warranty	1-Year Warranty
UPC	816904024529



HD+ INFLATOR 6 FT AIR HOSE

MODEL 10962-L

EXTRA LONG HOSE
heavy-duty and designed
for use in shops and on service trucks.