

COMMERCIAL GRADE SOCKET(S) - designed for commercial use

model 40306 | 40307 | 40308



17 mm | 19 mm | 21 mm



17 mm | 19 mm | 21 mm



MS17 15 mm | 19 mm | 22 mm
17 mm | 21 mm

IMPACT SOCKET SET (3-PIECE)

EXTRA DEEP WHEEL PROTECTOR,
1/2 IN. DRIVE

- Color-coded sockets for simple identification.
- Non-slip design for easy, accurate application.
- Durable sleeves protect wheels and nuts from marring or damage.
- The most popular size lug nuts in the performance market.
- Chamfered sockets easily attach to the nuts.

IMPACT SOCKET SET (3-PIECE)

EXTRA LONG THIN WALL DEEP WHEEL LUG,
1/2 IN. DRIVE

- The most popular size lug nuts in the performance market.
- 1/2" Drive Suitable for use with impact tool.
- Nylon sleeve and insert to prevent alloy wheel damage or marring.
- Color-coded sockets for simple identification.
- Extended socket length eliminates needs for torque extension.

IMPACT SOCKET SET (6-PIECE)

6PC SOCKET SET (DR.1/2", MS17 &
15/17/19/21/22MM)

- The most popular size lug nuts in the performance market.
- 1/2" Drive Suitable for use with impact tool.
- Nylon sleeve and insert to prevent alloy wheel damage or marring.
- Color-coded sockets for simple identification.

SPECIFICATIONS:	40306	40307	40308
Socket Size(s)*	1 PC 1/2 in. 17 mm 1 PC 1/2 in. 19 mm 1 PC 1/2 in. 21 mm	1 PC 1/2 in. 17 mm 1 PC 1/2 in. 19 mm 1 PC 1/2 in. 21 mm	1 PC 1/2 in. MS17 1 PC 1/2 in. 15 mm 1 PC 1/2 in. 17 mm 1 PC 1/2 in. 19 mm 1 PC 1/2 in. 21 mm 1 PC 1/2 in. 22 mm
Socket Color(s)	Blue (17 mm), Yellow (19 mm), Red (21 mm)	Blue (17 mm), Yellow (19 mm), Red (21 mm)	Assorted
Measurement System	Metric	Metric	Metric
Wall Thickness	Thin Wall	Thin Wall	Standard
Drive Size	1/2 in.	1/2 in.	1/2 in.
Socket(s) Length	3.25 in. 82.6 mm	6 in. 152.4 mm	3.5 in. 89 mm
Case Dimensions	5.75 (L) x 5 (W) x 1.75 in. (H) 146 x 127 x 44.5 mm	9 (L) x 5.5 (W) x 1.75 in. (H) 228.6 x 139.7 x 44.5 mm	12 (L) x 6.5 (W) x 1.75 in. (H) 305 x 177.8 x 50.8 mm
Includes	(3) Sockets, (3) Nylon Rim Protective Sleeves (Installed on Sockets), Case	(3) Sockets, (3) Nylon Rim Protective Sleeves (Installed), (3) Replacement Nylon Rim Protective Sleeves, Case	(6) Sockets, (6) Nylon Rim Protective Sleeves (Installed on Sockets), Case
Weight	2 lbs. 0.91 kg	3.25 lbs. 1.47 kg	4 lbs. 1.82 kg
Material	Designed with a long lasting material CR-MO (Chromium-Molybdenum) alloy steel		
Markets	Automotive, Performance, Shop	Automotive, Performance, Shop	Automotive, Performance, Shop
Warranty	Limited Lifetime	Limited Lifetime	Limited Lifetime
UPC	816904024895	816904024901	816904024918

* All designs are Nylon Protected Wheel CR-MO Socket(s)